

# Informal Quiz 5

T F

- ☐ ☐ A packet addressed to 225.13.40.3 will not leave the site (or administrative domain)
- ☐ ☐ SNMP is designed to fetch any subtree in a MIB in a single transaction
- ☐ ☐ The “SEQUENCE OF” constructor in ASN.1 syntax is used to define the equivalent of a “struct” in the C language.
- ☐ ☐ SNMP is only the message exchange protocol for network management.
- ☐ ☐ BOOTP extends RARP functionality and makes it independent of the link layer technology.
- ☐ ☐ The key difference between BOOTP and DHCP is that the latter can lease out addresses dynamically and for short periods

Rensselaer

Shivkumar Kalyanaraman

## Informal Quiz 5 (contd)

T F

- ☐ ☐ Application-layer relays provide multicast-like efficiencies in packet transmission, but incur management overhead
- ☐ ☐ A unidirectional shared tree reaching all destinations in a group is sufficient to support IP multicasting to that group.
- ☐ ☐ An IP multicast routing tree is built and maintained using the combination of IGMP (at the leaves) and a routing protocol
- ☐ ☐ The MBONE is suitable for multiway, highly interactive videoconferences
- ☐ ☐ Scalability in multicast routing is typically achieved by using shared trees and not requiring off-tree state.
- ☐ ☐ Changing IP (to IPv6) requires change to both the lower (link) and higher (transport) layers.

Rensselaer

Shivkumar Kalyanaraman

## Informal Quiz 5 (solns)

T F

- ✓ ☐ A packet addressed to 225.13.40.3 will not leave the site (or administrative domain)
- ☐ ✓ SNMP is designed to fetch any subtree in a MIB in a single transaction
- ☐ ✓ The “SEQUENCE OF” constructor in ASN.1 syntax is used to define the equivalent of a “struct” in the C language.
- ✓ ☐ SNMP is only the message exchange protocol for network management.
- ✓ ☐ BOOTP extends RARP functionality and makes it independent of the link layer technology.
- ✓ ☐ The key difference between BOOTP and DHCP is that the latter can lease out addresses dynamically and for short periods

Rensselaer

Shivkumar Kalyanaraman

## Informal Quiz 5 (contd)

T F

- ✓ ☐ Application-layer relays provide multicast-like efficiencies in packet transmission, but incur management overhead
- ☐ ✓ A unidirectional shared tree reaching all destinations in a group is sufficient to support IP multicasting to that group.
- ✓ ☐ An IP multicast routing tree is built and maintained using the combination of IGMP (at the leaves) and a routing protocol
- ☐ ✓ The MBONE is suitable for multiway, highly interactive videoconferences
- ✓ ☐ Scalability in multicast routing is typically achieved by using shared trees and not requiring off-tree state.
- ☐ ✓ Changing IP (to IPv6) requires change to both the lower (link) and higher (transport) layers.

Rensselaer

Shivkumar Kalyanaraman